


























































| ردیف | مدل  | مشخصات فنی   | تصویر   | قیمت (ریال) |
|------|--|--|---|-------------|
|      | <b>IP CAMERA</b>   |   | <b>NEW</b>  |             |
| 1    | TITAN 5000PWSF-SAF-NF  | <p>1/3" 5.0 Megapixel Starlight CMOS Sensor<br/>H265/H264 Encoding - Dual Stream<br/>2.8mm F1.6 Starlight Advance Fixed lens<br/>Main Stream 5MP (2880 * 1620) @ 20fps / 4MP @ 25fps<br/>Built in <b>Microphone</b><br/>Digital WDR, 3DNR, HLC, BLC<br/>30m Warmlight, 3 EXIR LED<br/>Standard Onvif (Compatible with Dahua, Hikvision, Maxron &amp; etc)<br/>Private Protocol With Z Series XVR<br/>Human Body Detection<br/>IP67 Metal Case, <b>Easy Installation</b>, 12VDC, <b>Smart PoE</b><br/>Fara View Mobile Monitoring, VMS Monitoring</p> |                  | 21,650,000  |
|      | <b>IP CAMERA</b>   |   | <b>NEW</b>  |             |
| 2    | AWASIS 5000PWLF-SAF-NF   | <p>1/3" 5.0 Megapixel Starlight CMOS Sensor<br/>H265/H264 Encoding - Dual Stream<br/>3.6mm F1.6 Starlight Advance Fixed lens<br/>Main Stream 5MP (2880 * 1620) @ 20fps / 4MP @ 25fps<br/>Built in <b>Microphone</b><br/>Digital WDR, 3DNR, HLC, BLC<br/>30m Warmlight, 3 EXIR LED<br/>Standard Onvif (Compatible with Dahua, Hikvision, Maxron &amp; etc)<br/>Private Protocol With Z Series XVR<br/>Human Body Detection<br/>IP67 Metal Case, 12VDC, <b>Smart PoE</b><br/>Fara View Mobile Monitoring, VMS Monitoring</p>                           |                  | 20,500,000  |
|      | <b>IP CAMERA</b>   |   | <b>NEW</b>  |             |
| 3    | KAVARIA 5000PWLF-SAF-NF  | <p>1/3" 5.0 Megapixel Starlight CMOS Sensor<br/>H265/H264 Encoding - Dual Stream<br/>3.6mm F1.6 Starlight Advance Fixed lens<br/>Main Stream 5MP (2880 * 1620) @ 20fps / 4MP @ 25fps<br/>Built in <b>Microphone</b><br/>Digital WDR, 3DNR, HLC, BLC<br/>50m Warmlight, 4 EXIR Power LED<br/>Standard Onvif (Compatible with Dahua, Hikvision, Maxron &amp; etc)<br/>Private Protocol With Z Series XVR<br/>Human Body Detection<br/>IP67 Metal Case, 12VDC, <b>Smart PoE</b><br/>Fara View Mobile Monitoring, VMS Monitoring</p>                     |                  | 23,850,000  |
| 4    | METIS 200ASF-SL  | <p>1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br/>3.6mm Fixed lens<br/>Resolution 1920(H) x 1080(V)<br/>DWDR, 3DNR, AWB, BLC<br/>30m IR Length, High Power LED<br/>OSD Menu by UTC (output 4-in-1)</p>  |                | 6,850,000   |
| 5    | DEVRA 200ASF-EL  | <p>1/2.9" CMOS Sensor, 2.0 Megapixel<br/>3.6mm Fixed lens<br/>Resolution 1920(H) x 1080(V)<br/>DWDR, 3DNR, AWB, BLC<br/>30m IR Length, High Power LED<br/>OSD Menu by UTC (output 4-in-1)</p>  |                | 6,750,000   |
| 6    | DEVRA 200ASF-SLA   | <p> HDTVI Camera<br/>1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br/>3.6mm Fixed lens<br/>Resolution 1920(H) x 1080(V)<br/>DWDR, 3DNR, AWB, BLC<br/>30m IR Length, 24 SMD LED<br/>Built in MIC<br/>OSD Menu by UTC (output 4-in-1)</p>  |                | 8,150,000   |
| 7    |  DEVRA 200DSF-SA  | <p> HDTVI Camera<br/>1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br/>2.8mm Fixed lens<br/>Resolution 1920(H) x 1080(V)<br/>DWDR, 3DNR, AWB, BLC<br/>30m Warmlight - 40m IR Length, 2 Dual LED<br/>Built in MIC<br/>OSD Menu by UTC (output 4-in-1)</p>  |                | 9,900,000   |
| 8    |  DEVRA 200DSF-SCA | <p> HDTVI Camera<br/>1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br/>2.8mm Fixed lens<br/>Resolution 1920(H) x 1080(V)<br/>DWDR, 3DNR, AWB, BLC<br/>30m Warmlight - 40m IR Length, 2 Dual LED<br/>Built in MIC, Support Audio In TVI &amp; <b>CVI</b> Mode (Compatible With Dahua Recorder)<br/>OSD Menu by UTC (output 4-in-1)</p>   | <b>NEW</b><br> | 9,900,000   |
| 9    | NORMA 200ASF-EL  | <p>1/2.9" CMOS Sensor, 2.0 Megapixel<br/>3.6mm Fixed lens<br/>Resolution 1920(H) x 1080(V)<br/>DWDR, 3DNR, AWB, BLC<br/>30m IR Length, 24 LED<br/>OSD Menu by UTC (output 4-in-1)<br/>IP66, Metal Case</p>   |                | 8,750,000   |








| ردیف | مدل  | مشخصات فنی  | تصویر   | قیمت (ریال) |
|------|--|---|---|-------------|
| 10   | NORMA 200ASF-SL  | 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br>3.6mm Fixed lens<br>Resolution 1920(H) × 1080(V)<br>DWDR, 3DNR, AWB, BLC<br>30m IR Length, 24 SMD LED<br>OSD Menu by UTC (output 4-in-1)<br>IP66, Metal Case   |                  | 9,150,000   |
| 11   |  NORMA 200WSF-S     | 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br>3.6mm F1.2 Starlight Fixed lens<br>Resolution 1920(H) × 1080(V)<br>DWDR, 3DNR, AWB, BLC<br>30m Warmlight Length, 2 Exir LED<br>OSD Menu by UTC(output 4-in-1)<br>IP66, Metal Case  |                  | 10,950,000  |
| 12   |  NORMA 200WSF-SA    | HDTVI Camera<br>1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br>2.8mm F1.2 Starlight Fixed lens<br>Resolution 1920(H) × 1080(V)<br>DWDR, 3DNR, AWB, BLC<br>30m Warmlight Length, 2 Exir LED<br>OSD Menu by UTC(output 4-in-1)<br>Built in MIC<br>IP66, Metal Case  |                  | 11,500,000  |
| 13   |  NORMA 500WSF-SA    | HDTVI Camera<br>1/2.8" Starlight CMOS Sensor, 5.0 Megapixel<br>2.8mm F1.2 Starlight Fixed lens<br>Resolution 2560(H) × 1920(V)<br>DWDR, 3DNR, AWB, BLC<br>30m Warmlight Length, 2 Exir LED<br>OSD Menu by UTC(output 4-in-1)<br>Built in MIC<br>IP66, Metal Case  |                  | 14,850,000  |
| 14   |  DORIS 200WSF-SA    | HDTVI Camera<br>1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br>2.8mm F1.2 Starlight Fixed lens<br>Resolution 1920(H) × 1080(V)<br>DWDR, 3DNR, AWB, BLC<br>40m Warmlight Length, 4 Array LED<br>OSD Menu by UTC (output 4-in-1)<br>Built in MIC  |                 | 9,260,000   |
| 15   |  LARIS 500DSF-SA  | HDTVI Camera<br>1/2.8" Starlight CMOS Sensor, 5.0 Megapixel<br>2.8mm F1.2 Starlight Fixed lens<br>Resolution 2560(H) × 1920(V)<br>DWDR, 3DNR, AWB, BLC<br>40m Warmlight - 50m IR Length, 4 Dual LED<br>OSD Menu by UTC(output 4-in-1)<br>Built in MIC<br>IP66, Metal Ball   |                | 15,200,000  |
| 16   | ARTEMIS 200ASF-SL  | 1/2.9" CMOS Sensor, 2.0 Megapixel<br>2.8mm F1.2 Starlight Fixed Lens<br>Resolution 1920(H) × 1080(V)<br>DWDR, 3DNR, AWB, BLC<br>OSD Menu by UTC (output 4-in-1)<br>45m IR Length, 24 SMD LED<br>IP66, Metal Case  | <br><b>NEW</b> | 9,430,000   |
| 17   |  TITAN 200DSF-SA  | HDTVI Camera<br>1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br>2.8mm F1.2 Starlight Fixed Lens<br>1920(H) × 1080(V) Resolution<br>DWDR, 3DNR, AWB, BLC<br>30m Warmlight- 40m IR Length, 3 Dual EXIR LED<br>OSD Menu by UTC(output 4-in-1)<br>Built in MIC<br>IP67, Metal Ball, Easy Installation  | <br><b>NEW</b> | 12,900,000  |
| 18   |  TITAN 500DSF-SA  | HDTVI Camera<br>1/2.8" Starlight CMOS Sensor, 5.0 Megapixel<br>2.8mm F1.2 Starlight Fixed Lens<br>2560(H) × 1920(V) Resolution<br>DWDR, 3DNR, AWB, BLC<br>30m Warmlight- 40m IR Length, 3 Dual EXIR LED<br>OSD Menu by UTC(output 4-in-1)<br>Built in MIC<br>IP67, Metal Ball, Easy Installation  | <br><b>NEW</b> | 15,650,000  |
| 19   |  TITAN 200WSF-SCA | HDTVI Camera<br>1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br>2.8mm F1.2 Starlight Fixed Lens<br>1920(H) × 1080(V) Resolution<br>DWDR, 3DNR, AWB, BLC<br>30m Warmlight, 3 Dual EXIR LED<br>OSD Menu by UTC(output 4-in-1)<br>Built in MIC, Support Audio In TVI & CVI Mode (Compatible With Dahua Recorder)<br>IP67, Metal Ball, Easy Installation | <br><b>NEW</b> | 12,200,000  |

| ردیف | مدل              | مشخصات فنی  | تصویر   | قیمت (ریال) |
|------|------------------|---|---|-------------|
| 20   | TITAN 500WSF-SA  | <p>HDTVI Camera<br/>1/2.8" Starlight CMOS Sensor, 5.0 Megapixel<br/>2.8mm F1.2 Starlight Fixed Lens<br/>2560(H) × 1920(V) Resolution<br/>DWDR, 3DNR, AWB, BLC<br/>30m Warmlight, 3 EXIR LED<br/>OSD Menu by UTC(output 4-in-1)<br/>Built in MIC<br/>IP67, Metal Ball, Easy Installation</p> |    | 15,100,000  |
| 21   | POLARIS 200WLF-S | <p>1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br/>3.6mm F1.2 Starlight Fixed lens<br/>Resolution 1920(H) × 1080(V)<br/>DWDR, 3DNR, AWB, BLC<br/>40m Warmlight, 4 EXIR LED<br/>OSD Menu by UTC(output 4-in-1)<br/>IP66, Metal Case, Easy Installation</p>                                   |    | 12,000,000  |
| 22   | NESTOR 200WLF-S  | <p>1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br/>3.6mm F1.2 Starlight Fixed lens<br/>Resolution 1920(H) × 1080(V)<br/>DWDR, 3DNR, AWB, BLC<br/>40m Warmlight, 4 EXIR LED<br/>OSD Menu by UTC(output 4-in-1)<br/>IP66, Metal Case</p>  |    | 12,000,000  |
| 23   | NESTOR 500WLF-SA | <p>HDTVI Camera<br/>1/2.8" Starlight CMOS Sensor, 5.0 Megapixel<br/>3.6mm F1.2 Starlight Fixed lens<br/>Resolution 2560(H) × 1920(V)<br/>DWDR, 3DNR, AWB, BLC<br/>40m Warmlight, 4 EXIR LED<br/>OSD Menu by UTC(output 4-in-1)<br/>Built in MIC<br/>IP66, Metal Case</p>                    |    | 15,450,000  |
| 24   | NESTOR 200DLF-S  | <p>1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br/>3.6mm F1.2 Starlight Fixed lens<br/>Resolution 1920(H) × 1080(V)<br/>DWDR, 3DNR, AWB, BLC<br/>40m Warmlight - 60m IR Length, 4 EXIR LED<br/>OSD Menu by UTC(output 4-in-1)<br/>IP66, Metal Case</p>                                      |   | 12,550,000  |
| 25   | NESTOR 500DLF-SA | <p>HDTVI Camera<br/>1/2.8" Starlight CMOS Sensor, 5.0 Megapixel<br/>3.6mm F1.2 Starlight Fixed lens<br/>Resolution 2560(H) × 1920(V)<br/>DWDR, 3DNR, AWB, BLC<br/>40m Warmlight - 60m IR Length, 4 EXIR LED<br/>OSD Menu by UTC(output 4-in-1)<br/>Built in MIC<br/>IP66, Metal Case</p>    |  | 16,000,000  |
| 26   | NESTOR 500DLF-S  | <p>HDTVI Camera<br/>1/2.8" Starlight CMOS Sensor, 5.0 Megapixel<br/>3.6mm F1.2 Starlight Fixed lens<br/>Resolution 2560(H) × 1920(V)<br/>DWDR, 3DNR, AWB, BLC<br/>40m Warmlight - 60m IR Length, 4 EXIR LED<br/>OSD Menu by UTC(output 4-in-1)<br/>IP66, Metal Case</p>                     |  | 15,550,000  |
| 27   | HELIX 200WLF-S   | <p>1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br/>3.6mm F1.2 Starlight Fixed lens<br/>Resolution 1920(H) × 1080(V)<br/>DWDR, 3DNR, AWB, BLC<br/>30m Warmlight Length, 3 EXIR LED<br/>OSD Menu by UTC(output 4-in-1)<br/>IP66, Metal Case</p>   |  | 11,300,000  |
| 28   | HELIX 200WLF-SA  | <p>HDTVI Camera<br/>1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br/>3.6mm F1.2 Starlight Fixed lens<br/>Resolution 1920(H) × 1080(V)<br/>DWDR, 3DNR, AWB, BLC<br/>30m Warmlight Length, 3 EXIR LED<br/>OSD Menu by UTC(output 4-in-1)<br/>Built in MIC<br/>IP66, Metal Case</p>             |  | 11,750,000  |
| 29   | HELIX 200DLF-S   | <p>1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br/>3.6mm F1.2 Starlight Fixed lens<br/>Resolution 1920(H) × 1080(V)<br/>DWDR, 3DNR, AWB, BLC<br/>30m Warmlight - 40m IR Length, 3 Dual EXIR LED<br/>OSD Menu by UTC(output 4-in-1)<br/>IP66, Metal Case</p>                                 |  | 11,750,000  |

| ردیف | مدل               | مشخصات فنی  | تصویر   | قیمت (ریال) |
|------|-------------------|---|---|-------------|
| 30   | HELIX 500DLF-S    | <p>1/2.8" Starlight CMOS Sensor, 5.0 Megapixel<br/>3.6mm F1.2 Starlight Fixed lens<br/>Resolution 2560(H) × 1920(V)<br/>DWDR, 3DNR, AWB, BLC<br/>30m Warmlight - 40m IR Length, 3 Dual EXIR LED<br/>OSD Menu by UTC(output 4-in-1)<br/>IP66, Metal Case</p>                                   |    | 14,750,000  |
| 31   | HELIX 500WLF-SA   | <p>1/2.8" Starlight CMOS Sensor, 5.0 Megapixel<br/>3.6mm F1.2 Starlight Fixed lens<br/>Resolution 2560(H) × 1920(V)<br/>DWDR, 3DNR, AWB, BLC<br/>30m Warmlight, 3 EXIR LED<br/>OSD Menu by UTC(output 4-in-1)<br/>Built in MIC<br/>IP66, Metal Case</p>                                       |    | 14,600,000  |
| 32   | AWASIS 200DLF-S   | <p>1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br/>3.6mm F1.2 Starlight Fixed lens<br/>Resolution 1920(H) × 1080(V)<br/>DWDR, 3DNR, AWB, BLC<br/>30m Warmlight - 40m IR Length, 3 Dual EXIR LED<br/>OSD Menu by UTC(output 4-in-1)<br/>IP66, Metal Case</p>                                   |    | 12,000,000  |
| 33   | AWASIS 500DLF-SA  | <p>HDTVI Camera<br/>1/2.8" Starlight CMOS Sensor, 5.0 Megapixel<br/>3.6mm F1.2 Starlight Fixed lens<br/>Resolution 2560(H) × 1920(V)<br/>DWDR, 3DNR, AWB, BLC<br/>30m Warmlight - 40m IR Length, 3 Dual EXIR LED<br/>OSD Menu by UTC(output 4-in-1)<br/>Built in MIC<br/>IP66, Metal Case</p> |    | 15,450,000  |
| 34   | AWASIS 500WLF-SA  | <p>HDTVI Camera<br/>1/2.8" Starlight CMOS Sensor, 5.0 Megapixel<br/>3.6mm F1.2 Starlight Fixed lens<br/>Resolution 2560(H) × 1920(V)<br/>DWDR, 3DNR, AWB, BLC<br/>30m Warmlight, 3 EXIR LED<br/>OSD Menu by UTC(output 4-in-1)<br/>Built in MIC<br/>IP66, Metal Case</p>                      |   | 14,850,000  |
| 35   | AWASIS 200WLF-S   | <p>1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br/>3.6mm F1.2 Starlight Fixed lens<br/>Resolution 1920(H) × 1080(V)<br/>DWDR, 3DNR, AWB, BLC<br/>30m Warmlight Length, 3 Exir LED<br/>OSD Menu by UTC(output 4-in-1)<br/>IP66, Metal Case</p>   |  | 11,500,000  |
| 36   | AWASIS 500WLF-S   | <p>1/2.5" Starlight CMOS Sensor, 5.0 Megapixel<br/>3.6mm F1.2 Starlight Fixed lens<br/>Resolution 3072(H) × 1728(V), 16:9<br/>DWDR, 3DNR, AWB, BLC<br/>30m Warmlight Length, 3 EXIR LED<br/>OSD Menu by UTC(output 4-in-1)<br/>IP66, Metal Case</p>   |  | 13,800,000  |
| 37   | Callisto 200WLF-S | <p>1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br/>3.6mm F1.2 Starlight Fixed lens<br/>Resolution 1920(H) × 1080(V)<br/>DWDR, 3DNR, AWB, BLC<br/>30m Warmlight Length, 4 Array LED<br/>OSD Menu by UTC(output 4-in-1)<br/>IP66, Metal Case</p>  |  | 10,950,000  |
| 38   | Callisto 500WLF-S | <p>1/2.5" Starlight CMOS Sensor, 5.0 Megapixel<br/>3.6mm F1.2 Starlight Fixed lens<br/>Resolution 3072(H) × 1728(V), 16:9<br/>DWDR, 3DNR, AWB, BLC<br/>30m Warmlight Length, 4 Array LED<br/>OSD Menu by UTC(output 4-in-1)<br/>IP66, Metal Case</p>  |  | 13,250,000  |
| 39   | CAPELLA 200ALF-EL | <p>1/2.9" CMOS Sensor, 2.0 Megapixel<br/>3.6 mm Fixed lens<br/>Resolution 1920(H) × 1080(V)<br/>DWDR, 3DNR, AWB, BLC<br/>35~40m IR Length, 6 Mini Array<br/>OSD Menu by UTC(output 4-in-1)<br/>IP66, Metal Case</p>   |  | 8,800,000   |
| 40   | CAPELLA 200ALF-SL | <p>1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br/>3.6 mm Fixed lens<br/>Resolution 1920(H) × 1080(V)<br/>DWDR, 3DNR, AWB, BLC<br/>35~40m IR Length, 6 Mini Array<br/>OSD Menu by UTC(output 4-in-1)<br/>IP66, Metal Case</p>   |  | 9,000,000   |
















| ردیف | مدل   | مشخصات فنی  | تصویر   | قیمت (ریال) |
|------|---|---|---|-------------|
| 41   |  CAPELLA 500ALF-S  | 1/2.5" Starlight Image Sensor, 5.0 Megapixel<br>3.6 mm F1.2 Starlight Fixed lens<br>Resolution 3072(H) × 1728(V), 16:9<br>DWDR, 3DNR, AWB, BLC<br>OSD Menu by UTC(output 4-in-1)<br>35~40m IR Length, 6 Mini Array<br>IP66, Metal Case    |    | 12,600,000  |
| 42   |  ERIS 200WLF-S     | 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br>3.6mm F1.2 Starlight Fixed lens<br>Resolution 1920(H) × 1080(V)<br>DWDR, 3DNR, AWB, BLC<br>30m Warmlight Length, 2 Power LED<br>OSD Menu by UTC(output 4-in-1)<br>IP66, Metal Case         |    | 11,000,000  |
| 43   |  ERINOM 200WLF-S   | 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br>3.6mm F1.2 Starlight Fixed lens<br>Resolution 1920(H) × 1080(V)<br>DWDR, 3DNR, AWB, BLC<br>25~30m Warmlight Length, 4 Power LED<br>OSD Menu by UTC(output 4-in-1)<br>IP66, Metal Case      |    | 11,100,000  |
| 44   | PARSIS 200ALF-EL  | 1/2.9" CMOS Sensor, 2.0 Megapixel<br>3.6mm Fixed lens<br>Resolution 1920(H) × 1080(V)<br>DWDR, 3DNR, AWB, BLC<br>30~35m IR Length, 6 Array LED<br>OSD Menu by UTC(output 4-in-1)<br>IP66, Metal Case                                      |    | 8,800,000   |
| 45   | PARSIS 200ALF-SL  | 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br>3.6mm Fixed lens<br>Resolution 1920(H) × 1080(V)<br>DWDR, 3DNR, AWB, BLC<br>30~35m IR Length, 6 Array LED<br>OSD Menu by UTC(output 4-in-1)<br>IP66, Metal Case                            |    | 9,000,000   |
| 46   |  PARSIS 200WLF-S  | 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br>3.6mm F1.2 Starlight Fixed lens<br>Resolution 1920(H) × 1080(V)<br>DWDR, 3DNR, AWB, BLC<br>30m Warmlight Length, 6 Array LED<br>OSD Menu by UTC(output 4-in-1)<br>IP66, Metal Case         |  | 10,550,000  |
| 47   |  PARSIS 500WLF-S | 1/2.5" Starlight Image Sensor, 5.0 Megapixel<br>3.6 mm F1.2 Starlight Fixed lens<br>Resolution 3072(H) × 1728(V), 16:9<br>DWDR, 3DNR, AWB, BLC<br>OSD Menu by UTC(output 4-in-1)<br>30m Warmlight Length, 6 Array LED<br>IP66, Metal Case |  | 12,950,000  |
| 48   | NARSIS 200ALF-EL  | 1/2.9" CMOS Sensor, 2.0 Megapixel<br>3.6mm Fixed lens<br>Resolution 1920(H) × 1080(V)<br>DWDR, 3DNR, AWB, BLC<br>40~45m IR Length, 8 Array LED<br>OSD Menu by UTC(output 4-in-1)<br>IP66, Metal Case                                      |  | 9,850,000   |
| 49   | NARSIS 200ALF-SL  | 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br>3.6mm Fixed lens<br>Resolution 1920(H) × 1080(V)<br>DWDR, 3DNR, AWB, BLC<br>40~45m IR Length, 8 Array LED<br>OSD Menu by UTC(output 4-in-1)<br>IP66, Metal Case                            |  | 10,150,000  |
| 50   |  NARSIS 500ALF-S | 1/2.5" Starlight Image Sensor, 5.0 Megapixel<br>3.6 mm F1.2 Starlight Fixed lens<br>Resolution 3072(H) × 1728(V), 16:9<br>DWDR, 3DNR, AWB, BLC<br>OSD Menu by UTC(output 4-in-1)<br>40~45m IR Length, 8 Array LED<br>IP66, Metal Case     |  | 12,550,000  |
| 51   | AVILON 200ALV-E   | 1/2.9" CMOS Sensor, 2.0 Megapixel<br>2.8~12mm Varifocal lens<br>Resolution 1932(H) × 1088(V)<br>DWDR, 3DNR, AWB, BLC<br>50~60m IR Length<br>OSD Menu by UTC(output 4-in-1)<br>IP66, Metal Case  |  | 16,850,000  |
| 52   | AVILON 500ALV-E   | 1/2.5" CMOS Sensor, 5.0 Megapixel<br>2.8~12 mm Varifocal lens<br>Resolution 2608(H) × 1952(V)<br>DWDR, 3DNR, AWB, BLC<br>OSD Menu by UTC(output 4-in-1)<br>50~60m IR Length<br>IP66, Metal Case   |  | 21,650,000  |

| ردیف | مدل  | مشخصات فنی   | تصویر   | قیمت (ریال) |
|------|--|--|---|-------------|
| 53   |  NESO 200WLF-S    | 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br>3.6mm F1.2 Starlight Fixed lens<br>Resolution 1920(H) × 1080(V)<br>DWDR, 3DNR, AWB, BLC<br>60m Warmlight Length, 8 Power LED<br>OSD Menu by UTC(output 4-in-1)<br>IP66, Metal Case  |                  | 13,700,000  |
| 54   |  KAVARIA 200WLF-S | 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br>3.6mm F1.2 Starlight Fixed lens<br>Resolution 1920(H) × 1080(V)<br>DWDR, 3DNR, AWB, BLC<br>50m Warmlight Length, 4 Power LED<br>OSD Menu by UTC(output 4-in-1)<br>IP66, Metal Case  |                  | 13,800,000  |
| 55   |  KAVARIA 500WLF-S | 1/2.8" Starlight CMOS Sensor, 5.0 Megapixel<br>3.6mm F1.2 Starlight Fixed lens<br>Resolution 2560(H) × 1920(V)<br>DWDR, 3DNR, AWB, BLC<br>50m Warmlight Length, 4 Power LED<br>OSD Menu by UTC(output 4-in-1)<br>IP66, Metal Case  |                  | 16,100,000  |
| 56   |  KAVARIA 200ALF-S | 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel<br>3.6mm F1.2 Starlight Fixed lens<br>Resolution 1920(H) × 1080(V)<br>DWDR, 3DNR, AWB, BLC<br>70-80m IR Length , High Power LED<br>OSD Menu by UTC(output 4-in-1)<br>IP66, Metal Case  |                  | 11,750,000  |
| 57   |  KAVARIA 500ALF-S | 1/2.5" Starlight CMOS Sensor, 5.0 Megapixel<br>3.6mm F1.2 Starlight Fixed lens<br>Resolution 3072(H) × 1728(V), 16:9<br>DWDR, 3DNR, AWB, BLC<br>70-80m IR Length , High Power LED<br>OSD Menu by UTC(output 4-in-1)<br>IP66, Metal Case  |                  | 14,750,000  |
| 58   | FARA AI ALARM BOX  | 3 Output Relay Box<br>1 Output With 12VDC<br>1 RJ45 Web Management Interface<br>Compatible With Z Series XVR<br>12VDC Input (Without Adaptor)  | <br><b>NEW</b> | 13,800,000  |
|      |  | این محصول به وسیله کابل شبکه به رکوردرهای سری زد متصل شده و با تعریف و پیاده سازی سناریوهای مختلف از طریق رکوردر و منوی خود محصول می توان از قابلیت های تشخیص انسان و خودروی دوربین و رکوردر در جهت فعال سازی خروجی محصول استفاده نمود تا خروجی تجهیزاتی از قبیل آزر، تلفن کننده، فرمان به دزدگیر و سایر تجهیزات فرمان پذیر را فعل کرد و از دوربین ها به عنوان دکتور محیطی با هوش مصنوعی و دقت بسیار بالا استفاده نمود   |   |             |
| 59   |  OHD-6104XF-A1  | 4CH H.265 5MP-Lite XVR<br>4CH AHD Camera(HD Mode), 16CH 5MP IP Camera (IP Mode)<br>Preview Capacity: 4*(5MP-Lite@20fps/4MP-Lite@25fps/1080P@25fps)<br>Code Capacity: 4*(5MP-Lite@12fps/4MP-Lite@17fps/1080P@18fps/1080P-Lite@25fps)<br>4CH Playback<br>Support AOC (Audio Over Coaxial For All Channel)<br>Pentabrid (Analoge,AHD,CVI,TVI,IP)<br>HDMI & VGA Video Output<br>1 SATA HDD Up to 8TB<br>1CH Audio In/1CH Audio Out<br>2*USB 2.0, 1*10/100 Mbps LAN Interface<br>P2P support, Onvif 2.4, IOS-Andriod Mobile APP & CMS PC Software   |                | 22,900,000  |
| 60   |  OHD-4104ZF-A1  | 4CH H.265 1080P-Lite XVR<br>Preview Capacity: 4*1080P-Lite@25fps<br>Code Capacity: 4*1080P-Lite@24fps<br>2CH Playback<br>Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)<br>Pentabrid (Analoge,AHD,CVI,TVI,IP)<br>HDMI & VGA Video Simultaneous Output<br>1 SATA HDD Up to 10TB<br>1CH Audio In/1CH Audio Out<br>2*USB 2.0, 1*10/100 Mbps LAN Interface<br>P2P support, IOS-Andriod FARA VIEW App - Adaptive Iran & International Servers   |                | 20,900,000  |
| 61   |  OHD-6104ZF-A1  | 4CH AHD H.265 5MP-Lite XVR<br>4CH AHD Camera + 1CH IP Camera<br>Preview Capacity: 4*(5MP-Lite@20fps)<br>Code Capacity: 4*(5MP-Lite@12fps/4MP-Lite@17fps/1080P@15fps/1080P-Lite@25fps)<br>4CH Playback<br>Support SMD (Human/Vehicle Clasification For 4CH)<br>Support face detection 1CH (With Special Firmware Upgarde / Not At The Same Time As SMD)<br>Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)<br>Pentabrid (Analoge,AHD,CVI,TVI,IP)<br>HDMI & VGA Video Simultaneous Output<br>1 SATA HDD Up to 10TB<br>1CH Audio In/1CH Audio Out<br>2*USB 2.0, 1*10/100 Mbps LAN Interface<br>P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App Adaptive Iran & International Servers |                | 25,400,000  |

| ردیف | مدل                | مشخصات فنی  | تصویر  | قیمت (ریال) |
|------|--------------------|---|--|-------------|
| 62   | OHD-6104ZFN-A1     | <p><b>SMD</b> 4CH H.265 5MP-Lite XVR<br/>4CH Camera + 1CH IP Camera<br/>Preview Capacity: 4*5MP-Lite@20fps<br/>Code Capacity: 4*(5MP-Lite@12fps/4MP-Lite@17fps/1080P@15fps/1080P-Lite@25fps)<br/>4CH Playback<br/>Support SMD (Human/Vehicle Classification For 4CH)<br/>Support face detection 1CH (With Special Firmware Upgrade / Not At The Same Time As SMD)<br/>Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)<br/>Pentabrid (Analoge,AHD,CVI,TVI,IP)<br/>HDMI &amp; VGA Video Simultaneous Output<br/>1 SATA HDD Up to 10TB<br/>1CH Audio In/1CH Audio Out<br/>2*USB 2.0, 1*10/100 Mbps LAN Interface<br/>P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran &amp; International Servers</p> | <br> | 25,400,000  |
| 63   | OHD-8104ZFN-4KL/A4 | <p><b>SMD</b> 4CH H.265 Real 5MP XVR<br/>4CH Camera (Analog &amp; IP)<br/>Preview Capacity: 4*5MP@12fps<br/>Code Capacity: 4*(5MP@12fps/4MP@15fps/1080P@25fps)<br/>4CH Playback<br/>Support SMD (Human/Vehicle Classification For 4CH)<br/>Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)<br/>Pentabrid (Analoge,AHD,CVI,TVI,IP)<br/>HDMI 4K &amp; VGA Video Simultaneous Output - Analog Video Output (BNC)<br/>1 SATA HDD Up to 10TB<br/>4CH Audio In/1CH Audio Out<br/>2*USB 2.0, 1*10/100 Mbps LAN Interface<br/>P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran &amp; International Servers</p>   | <br> | 35,700,000  |
| 64   | OHD-8104ZF-4KL/A4  | <p><b>SMD</b> 4CH H.265 Real 5MP XVR<br/>4CH Camera (Analog &amp; IP)<br/>Preview Capacity: 4*5MP@12fps<br/>Code Capacity: 4*(5MP@12fps/4MP@15fps/1080P@25fps)<br/>4CH Playback<br/>Support SMD (Human/Vehicle Classification For 4CH)<br/>Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)<br/>Pentabrid (Analoge,AHD,CVI,TVI,IP)<br/>HDMI 4K &amp; VGA Video Simultaneous Output - Analog Video Output (BNC)<br/>1 SATA HDD Up to 10TB<br/>4CH Audio In/1CH Audio Out<br/>2*USB 2.0, 1*10/100 Mbps LAN Interface<br/>P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran &amp; International Servers</p>   |   | 35,700,000  |
| 65   | OHD-6104XH-A1      | <p>4CH H.265 5MP-Lite XVR<br/>4CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode)<br/>Preview Capacity:4*(5MP-Lite@20fps/4MP-Lite@25fps/1080P@25fps)<br/>Code Capacity: 4*(5MP-Lite@8fps/4MP-Lite@15fps/1080P@18fps/1080P-Lite@25fps)<br/>4CH Playback<br/>Support real-time face detection, Face list, Face playback<br/>Pentabrid (Analoge,AHD,CVI,TVI,IP)<br/>HDMI &amp; VGA Video Output<br/>1 SATA HDD Up to 6TB<br/>1CH Audio In/1CH Audio Out<br/>2*USB 2.0, 1*10/100 Mbps LAN Interface<br/>P2P support, IOS-Andriod Mobile APP &amp; CMS PC Software</p>   |   | 25,400,000  |
| 66   | OHD-6108XF-A1      | <p>8CH H.265 5MP-Lite XVR<br/>8CH AHD Camera(HD Mode), 16CH 5MP IP Camera (IP Mode)<br/>Preview Capacity: 8*(5MP-Lite@12fps/4MP-Lite@15fps/1080P-Lite@25fps)<br/>Code Capacity: 8*(5MP-Lite@5fps/4MP-Lite@8fps/1080P-Lite@15fps)<br/>8CH Playback<br/>Support AOC (Audio Over Coaxial For All Channel)<br/>Pentabrid (Analoge,AHD,CVI,TVI,IP)<br/>HDMI &amp; VGA Video Output<br/>1 SATA HDD Up to 8TB<br/>1CH Audio In/1CH Audio Out<br/>2*USB 2.0, 1*10/100 Mbps LAN Interface<br/>P2P support, Onvif 2.4<br/>IOS-Andriod Mobile APP &amp; CMS PC Software</p>  |   | 28,750,000  |
| 67   | OHD-6108ZF-A1      | <p><b>SMD</b> 8CH AHD H.265 5MP-Lite XVR<br/>8CH AHD Camera + 2CH IP Camera<br/>Preview Capacity: 8*5MP-Lite@12fps<br/>Code Capacity: 8*(5MP-Lite@6fps/4MP-Lite@8fps/1080P-Lite@16fps)<br/>8CH Playback<br/>Support SMD (Human/Vehicle Classification For 4CH)<br/>Support face detection 1CH (With Special Firmware Upgrade / Not At The Same Time As SMD)<br/>Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)<br/>Pentabrid (Analoge,AHD,CVI,TVI,IP)<br/>HDMI &amp; VGA Video Simultaneous Output<br/>1 SATA HDD Up to 10TB<br/>1CH Audio In / 1CH Audio Out<br/>2*USB 2.0, 1*10/100 Mbps LAN Interface<br/>P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App Adaptive Iran &amp; International Servers</p>      |   | 32,800,000  |

| ردیف | مدل                | مشخصات فنی   | تصویر  | قیمت (ریال) |
|------|--------------------|--|--|-------------|
| 68   | OHD-6108ZFN-A1     | <p><b>SMD</b> 8CH H.265 5MP-Lite XVR<br/>8CH Camera + 2CH IP Camera<br/>Preview Capacity: 8*5MP-Lite@12fps<br/>Code Capacity: 8*(5MP-Lite@6fps/4MP-Lite@8fps/1080P-Lite@16fps)<br/>8CH Playback<br/>Support SMD (Human/Vehicle Classification For 8CH)<br/>Support face detection 1CH (With Special Firmware Upgrade / Not At The Same Time As SMD)<br/>Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)<br/>Pentabrid (Analoge,AHD,CVI,TVI,IP)<br/>HDMI &amp; VGA Video Simultaneous Output<br/>1 SATA HDD Up to 10TB<br/>1CH Audio In/1CH Audio Out<br/>2*USB 2.0, 1*10/100 Mbps LAN Interface<br/>P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App - Adaptive Iran &amp; International Servers</p>   | <br> | 32,800,000  |
| 69   | OHD-8108ZFN-4KL/A4 | <p><b>SMD</b> 8CH H.265 4K-Lite &amp; Real 5MP XVR<br/>8CH Camera + 2CH IP<br/>Preview Capacity: 8*(4K-Lite@15fps/5MP@12fps)<br/>Code Capacity: 8*(4K-Lite@9fps/5MP@8fps/4MP@10fps/1080P@20fps)<br/>8CH Playback<br/>Support SMD (Human/Vehicle Classification For 8CH)<br/>Support face detection 1CH (With Special Firmware Upgrade / Not At The Same Time As SMD)<br/>Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)<br/>Pentabrid (Analoge,AHD,CVI,TVI,IP)<br/>HDMI 4K &amp; VGA Video Simultaneous Output - Analog Video Output (BNC)<br/>1 SATA HDD Up to 10TB<br/>4CH Audio In/1CH Audio Out<br/>2*USB 2.0, 1*10/100 Mbps LAN Interface<br/>P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran &amp; International Servers</p>  | <br> | 52,350,000  |
| 70   | OHD-8208ZF-4KL/A4  | <p><b>SMD</b> 8CH H.265 4K-Lite &amp; Real 5MP XVR<br/>8CH Camera + 2CH IP<br/>Preview Capacity: 8*(4K-Lite@15fps/5MP@12fps)<br/>Code Capacity: 8*(4K-Lite@9fps/5MP@8fps/4MP@10fps/1080P@20fps)<br/>8CH Playback<br/>Support SMD (Human/Vehicle Classification For 8CH)<br/>Support face detection 1CH (With Special Firmware Upgrade / Not At The Same Time As SMD)<br/>Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)<br/>Pentabrid (Analoge,AHD,CVI,TVI,IP)<br/>HDMI 4K &amp; VGA Video Simultaneous Output - Analog Video Output (BNC)<br/>2 SATA HDD Up to 10TB For each port (Change Adaptur to 12V/5A)<br/>4CH Audio In/1CH Audio Out<br/>2*USB 2.0, 1*10/100 Mbps LAN Interface<br/>P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran &amp; International Servers</p> |   | 52,350,000  |
| 71   | OHD-6108XH-A1      | <p>8CH AHD H.265 5MP-Lite XVR<br/>8CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode)<br/>Preview Capacity:8*(5MP-Lite@12fps/4MP-Lite@15fps/1080P-Lite@25fps)<br/>Code Capacity:8*(5MP-Lite@6fps/4MP-Lite@8fps/1080P@8fps/1080P-Lite@15fps)<br/>8CH Playback:4ch main stream/8ch sub-stream<br/>Support real-time face detection, Face list, Face playback<br/>Pentabrid (Analoge,AHD,CVI,TVI,IP)<br/>HDMI &amp; VGA Video Output<br/>1 SATA HDD Up to 6TB<br/>1CH Audio In/1CH Audio Out<br/>2*USB 2.0, 1*10/100 Mbps LAN Interface<br/>P2P support, IOS-Andriod Mobile APP &amp; CMS PC Software</p>   |   | 33,150,000  |
| 72   | OHD-6108XH-A4      | <p>8CH AHD H.265 5MP-Lite XVR<br/>8CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode)<br/>Preview Capacity:8*(5MP-Lite@12fps/4MP-Lite@15fps/1080P-Lite@25fps)<br/>Code Capacity:8*(5MP-Lite@6fps/4MP-Lite@8fps/1080P@8fps/1080P-Lite@15fps)<br/>8CH Playback:4ch main stream/8ch sub-stream<br/>Support real-time face detection, Face list, Face playback<br/>Pentabrid (Analoge,AHD,CVI,TVI,IP)<br/>HDMI &amp; VGA Video Output<br/>1 SATA HDD Up to 6TB<br/>4CH Audio In/1CH Audio Out<br/>2*USB 2.0, 1*10/100 Mbps LAN Interface<br/>P2P support, IOS-Andriod Mobile APP &amp; CMS PC Software</p>   |   | 33,600,000  |
| 73   | OHD-6216ZF-A1      | <p><b>SMD</b> 16CH AHD H.265 5MP-Lite XVR<br/>16CH AHD Camera + 4CH IP Camera<br/>Preview Capacity:16*5MP-Lite@12fps<br/>Code Capacity:16*(5MP-Lite@6fps/4MP-Lite@8fps/1080P-Lite@16fps)<br/>16CH Playback<br/>Support SMD (Human/Vehicle Classification For 8CH)<br/>Support face detection 1CH (With Special Firmware Upgrade / Not At The Same Time As SMD)<br/>Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)<br/>Pentabrid (Analoge,AHD,CVI,TVI,IP)<br/>HDMI &amp; VGA Video Simultaneous Output<br/>2 SATA HDD Up to 10TB for each port<br/>1CH Audio In/1CH Audio Out<br/>2*USB 2.0, 1*10/100 Mbps LAN Interface<br/>P2P support, IOS-Andriod FARA VIEW App Adaptive Iran &amp; International Servers</p>   |   | 56,950,000  |



| ردیف | مدل                | مشخصات فنی  | تصویر  | قیمت (ریال) |
|------|--------------------|---|--|-------------|
| 74   | OHD-6116ZFN-A1     | <p><b>SMD</b>  </p> <p>16CH H.265 5MP-Lite XVR<br/>16CH Camera + 4CH IP Camera<br/>Preview Capacity:16*5MP-Lite@12fps<br/>Code Capacity:16*(5MP-Lite@6fps/4MP-Lite@8fps/1080P-Lite@16fps)<br/>16CH Playback<br/>Support SMD (Human/Vehicle Classification For 16CH)<br/>Support face detection 1CH (With Special Firmware Upgrade / Not At The Same Time As SMD)<br/>Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)<br/>Pentabrid (Analoge,AHD,CVI,TVI,IP)<br/>HDMI &amp; VGA Video Simultaneous Output<br/>1 SATA HDD Up to 10TB<br/>1CH Audio In/1CH Audio Out<br/>2*USB 2.0, 1*10/100 Mbps LAN Interface<br/>P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App - Adaptive Iran &amp; International Servers</p>                       | <br> | 56,200,000  |
| 75   | OHD-6108ZHN-A4     | <p><b>SMD</b>  <br/><b>HISILICON</b><br/><b>NEW AI Chipset</b></p> <p>8CH H.265 5MP-Lite XVR<br/>8CH Camera (Analog &amp; IP)<br/>Preview Capacity: 8*5MP-Lite@20fps<br/>Code Capacity: 8*(5MP-Lite@12fps)<br/>8CH Playback (4CH@12fps + 4CH@1fps)<br/>Support SMD (Human/Vehicle Classification For 8CH)<br/>Support face detection 1CH<br/>Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)<br/>Pentabrid (Analoge,AHD,CVI,TVI,IP)<br/>HDMI &amp; VGA Video Simultaneous Output<br/>1 SATA HDD Up to 10TB<br/>4/1 CH Audio In/Out - 2*USB - 1*10/100 Mbps LAN Interface<br/>P2P support, Onvif<br/>IOS-Andriod FARA VIEW App - Adaptive Iran &amp; International Servers</p>  | <br> | 35,900,000  |
| 76   | OHD-8116ZHN-4KL/A4 | <p><b>SMD</b>  <br/><b>HISILICON</b><br/><b>NEW AI Chipset</b></p> <p>16CH H.265 4K-Lite &amp; Real 5MP XVR<br/>16CH Camera (Analog &amp; IP)<br/>Preview Capacity: 16*(4K-Lite@15fps/5MP@12fps)<br/>Code Capacity: 16*(4K-Lite@7fps/5MP@8fps)<br/>16CH Playback<br/>Support SMD (Human/Vehicle Classification For 16CH)<br/>Support 1CH face detection<br/>Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)<br/>Pentabrid (Analoge,AHD,CVI,TVI,IP)<br/>HDMI 4K &amp; VGA Video Simultaneous Output - Analog Video Output (BNC)<br/>1 SATA HDD Up to 10TB<br/>4CH Audio In/1CH Audio Out<br/>2*USB 2.0, 1*10/100 Mbps LAN Interface<br/>P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App - Adaptive Iran &amp; International Servers</p> | <br> | 79,350,000  |
| 77   | OHD-6216XH-A4      | <p>16CH H.265 5MP-Lite XVR<br/>16CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode)<br/>Preview Capacity:16*(5MP-Lite@12fps/4MP-Lite@15fps/1080P-Lite@25fps)<br/>Code Capacity:16*(5MP-Lite@6fps/4MP-Lite@8fps/1080P@8fps/1080P-Lite@15fps)<br/>16CH Playback<br/>Support real-time face detection, Face list and Face playback<br/>Pentabrid (Analoge,AHD,CVI,TVI,IP)<br/>HDMI &amp; VGA Video Output<br/>2 SATA HDD Up to 6TB for each port<br/>4CH Audio In/1CH Audio Out<br/>2*USB 2.0, 1*10/100 Mbps LAN Interface<br/>P2P support, IOS-Andriod Mobile APP &amp; CMS PC Software</p>   |   | 56,950,000  |
| 78   | OHD-8216X-A2       | <p><b>AI</b> </p> <p>16CH H.265 8MP-Lite XVR<br/>16CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode)<br/>Preview Capacity: 16*(8MP-Lite@15fps/5MP@12fps/5MP-Lite@20fps/4MP@15fps/3MP@18fps/4MP-Lite/3MP-Lite/1080P/720P@25fps)<br/>Code Capacity: 16*(8MP-Lite@8fps/5MP@6fps/5MP-Lite@12fps/4MP@8fps/3MP@10fps/3MP-Lite@18fps/4MP-Lite/1080P@15fps/720P@25fp)<br/>16CH Playback<br/>Support real-time face detection, Face list and Face playback<br/>AI Functions: Intrusion , Line crossing<br/>Support Phone push on Mobile app<br/>Pentabrid (Analoge,AHD,CVI,TVI,IP)<br/>HDMI &amp; VGA Video Output<br/>2 SATA HDD Up to 6TB for each port<br/>2CH Audio In/1CH Audio Out<br/>2*USB 2.0, 1*10/100 Mbps LAN Interface<br/>P2P support, IOS-Andriod Mobile APP &amp; CMS PC Software<br/>Wireless Mouse</p>                             |   | 78,200,000  |